Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder , double anti-corrosion to extend service life. This lawn lamp series uses LED. High efficiency constant current driver, ensure the light source is maximum used.

FIELDS OF APPLICATION
Office & Education, offices, open-plan offices, conference rooms, conference rooms, reception areas, counters, galleries, hotels, restaurants, living spaces

IEC 62717 LED-modules for general lighting – Performance requirements
IEC 62722-2-1 Particular requirements for LED luminaires

High Lumen Efficacy
Body - Die cast aluminum
Diffuser - Frosted Acrylic
Glowing Wire Test - 850°
Temperature - ta=20 °C ~ ta max=50 °C
Class - III

Model --- E 310



A - Ø153 X 100 mm / Cutout - Ø135

B - Ø223 X 100 mm / Cutout - Ø205

Default Available

22E310-W-30-180-0-A

Product Assistant Chart

E310XXXXX

- Size — A — B — [ ]
- Driver — 0 On/Off — 1 Dali — 2 Dimmable — 3 Phase Dimming — 4 1-10 — [ ]
- Beam Angle — 180° — [ ]
- Kelvin — 30 3000K — 40 4000K — 60 6000K — [ ]
- Finishing — W White — CH Chrome — G Gold — MF Matt Finishe — [ ]
- Wattage — 22 — 32 — 42 — [ ]

Lighting Customization Solution offer the wide range of customized product with best available options.

IP 54 **COB** **McA Step 3** **220~240V**

Accessories



Explanation of the three curves:
V(λ) = Perception of brightness, daytime seeing with the cones
V'(λ) = Night-time seeing with the rods
$S_{mel}(\lambda)$ = Melatonin suppression with the photosensitive ganglion cells



LED life time			Operating time 1.000 h									
Lamp Lumen Maintenance Factor			1	10	20	30	40	50	60	70	80	90	100
Lamp Survival Factor			1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
		LSF	1	1	1	1	1	1	1	0.99	0.99	0.99	0.99

A++ ENERGY LEVEL · LED · CRI>90 · series wiring · RoHS COMPLIANT · CIDET · LM-80 · FLICKER FREE