



Zoom Track Light



Indoor Application - Track Light



Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder, double anti-corrosion to extend service life. This lawn lamp series uses LED. High efficiency constant current driver, ensure the light source is maximum used.

FIELDS OF APPLICATION


Office & Education, offices, open-plan offices, conference rooms, conference rooms, reception areas, counters, galleries, hotels, restaurants, living spaces

IEC 62717 LED-modules for general lighting – Performance requirements
IEC 62722-2-1 Particular requirements for LED luminaires

High Lumen Efficacy
Body - Die cast extruded aluminum
Diffuser - Polycarbonate
Glowing Wire Test - 650°
Temperature - ta=20 °C ~ ta max=50 °C
Class - I

Optional optical diffusers -  
Clear Frosted

Model ----- **K33**



A - Ø55 - 158.84mm

Default Available

15K33-B-30-16-0-A 

Product Assistant Chart




K33	X	X	X	X	X
Size	A				
Driver	0	1	2	3	4
	On/Off	Dali	Dimmable	Phase Dimming	1-10
Beam Angle (Lumen/W)	16° 70°				
Kelvin	27	30	40	50	60
	2700K	3000K	4000K	5000K	6000K
Finishing	W		G		B
	White		Dark Grey		Black
Wattage	15				

Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.


IP 44 IK 08 COB McA Step 3 220~240V

Relative spectral perception of brightness and melanopic effect

Effect as a percentage



Explanation of the three curves:
V(A) = Perception of brightness, daytime seeing with the cones
V(A) = Night-time seeing with the rods
S_m(A) = Melatonin suppression with the photosensitive ganglion cells



LED life time			Operating time 1.000 h										
Lamp Lumen Maintenance Factor			1	10	20	30	40	50	60	70	80	90	100
Lamp Survival Factor			1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99	0.98
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
		LSF	1	1	1	1	1	1	1	0.99	0.99	0.99	0.99



LED



series wiring



CE

